

## Sapa Folding door 2086 / 2086 SX

Isolated doorpart in aluminium Sapa Folding Door 2086/ 2086 SX.  
Profile depth 86 mm.  
Outward opening/ inward opening, with 3/ 4/ 5/ 6 folding segments.  
Narrow section/ modular section.  
Rebate insulated seal  
Surface treatment anodizing Nature/ HX5/ HX 10/ HX 20/ HX 30/ HX 40/ HX 50.  
Surface treatment powder coating 60  $\mu\text{m}$ , pretreatment acc. to Sapa std. Color NCS S/ RAL.  
Double glass/ Triple glass/ toughened/ laminated/ sunscreen.  
Infill panel F1/ F2/ F3/ F4 acc. to Sapa std.  
Max. U-value for the whole construction.  
Sound insulation: Rw/ Rw+Ctr.  
Hinges, espagnolette, flushbolt and roller fitting acc. to Sapa std.  
Door handle.  
Lock.  
Lock striker acc. to Sapa std.  
Installation and connections acc. to Sapa instructions.

Instructions.

Select alternative.

Select alternative.

Select alternative.

Select one type.

Select color.

Select alternative. Glass thickness 20-64mm.

Select finishes.

Select U-value.

Select type and dB.

Select type.

Select type.