

# Sapa Door 2050 with E-frame

Instructions.

Unisolated doorpart: in aluminium Sapa Door 2050 with E-frame.  
Profile depth 50 mm.  
Access control system, E-frame.  
Outward opening/ inward opening, single door/ double door/ meeting door.  
Narrow section/ modular section.  
Non finger trapping function.  
Rebate seal/ wool pile/ without threshold.  
Surface treatment anodizing nature/ HX 10/ HX 20/ HX 30/ HX 40/ HX 50.  
Surface treatment powder coating 60 µm, pretreatment acc. to Sapa std. Color NCS S/ RAL.  
Single glass/ double glass/ toughened/ laminated.  
Infill panel F1/ F2/ F3/ F4/ F5 acc. to Sapa std.  
Hinges/ barrel hinges.  
Pull handle/ push handle/ door handle.  
Lock.  
Lock striker.  
Electric strikes.  
Wiring loop.  
Motor lock.  
Door closing device.  
Automatic door opening device.  
Panic or emergency device.  
Flushbolt, single action/ double action acc. to Sapa std.  
Automatic flushbolt acc. to Sapa std.  
Door coordinator.  
Installation and connections acc. to Sapa instructions.

Select alternative.  
Select one alternative.  
Or nor. Is not provided with barrel hinge.  
Select alternative.  
Select one type.  
Select color.  
Select alternative. Glass thickness 3-33mm.  
Select finishes.  
Select one alternative and surface treatment.  
Select type.  
Select type.  
Select type.  
Select type and function.  
Select type.  
Select type.  
Select type.  
With double door.  
With double door.  
Select type. With double door.