

Sapa Door 2050 design

Instructions.

Unisolated doorpart in aluminium Sapa Door 2050 design.
Profile depth 50 mm.
Outward opening/ inward opening, single door/ double door.
Narrow section.
Rebate seal/ wool pile/ without threshold.
Surface treatment anodizing nature/ HX 10/ HX 20/ HX 30/ HX 40/ HX 50.
Surface treatment powder coating 60 μm , pretreatment acc. to Sapa std. Color NCS S/ RAL.
Symmetricallt installed single glass/ toughened/ laminated.
L-shaped/ bevelled/ rectangular glazing bead.
Barrel hinges/ hinges.
Pull handle/ push handle/ door handle.
Lock.
Lock striker.
Electric strikes.
Wiring loop.
Motor lock.
Door closing device.
Automatic door opening device.
Panic or emergency device.
Flushbolt, single action/ double action acc. to Sapa std.
Automatic flushbolt acc. to Sapa std.
Door coordinator.
Installation and connections acc. to Sapa instructions.

Select alternative.
Select one type.
Select color.
Select alternative. Glass thickness 5-10mm.
Select alternative.
Select one alternative.
Select type.
Select type.
Select type.
Select type and function.
Select type.
Select type and function.
Select type.
Select type.
Select type.
With double door.
With double door.
Select type. With double door.