

Sapa Door 2086

Instructions.

Isolated doorparti in aluminium Sapa Door 2086.
Profile depth 86 mm.
Outward opening/ inward opening, single door/ double door/ meeting door.
Narrow section/ modular section.
Non finger trapping function.
Rebate seal/ wool pile/ without threshold.
Surface treatment anodizing nature/ HX 5/HX 10/ HX 20/ HX 30/ HX 40/ HX 50.
Surface treatment powder coating 60 µm, pretreatment acc. to Sapa std. Color NCS S/ RAL.
Double glass/ Triple glass/ toughened/ laminated/ sunscreen.
Infill panel F1/ F2/ F3/ F4, acc. to Sapa std.
Max. U-value for the whole construction.
Air tightness: no class/ class 2/ class 4, acc. to EN 12207.
Water tightness: no class/ class 4A/ class 9A, acc. to EN 12208.
Sound insulation: Rw/ Rw+Ctr.
Hinges/ barrel hinges/ hidden hinges.
Pull handle/ push handle/ door handle.
Lock.
Lock striker.
Electric strikes.
Wiring loop.
Motor lock.
Door closing device.
Automatic door opening device.
Panic or emergency device.
Flushbolt, single action/ double action, acc. to Sapa std.
Automatic flushbolt, acc. to Sapa std.
Door coordinator.
Installation and connections, acc. to Sapa instructions.

Select alternative.
Select one alternative.
Or not. Is not provided with barrel hinge.
Select alternative.
Select one type.
Select color.
Select alternative. Glass thickness 20-64mm.
Select finishes.
Select U-value.
Select class.
Select class.
Select type and dB.
Select one alternative and surface treatment.
Select type.
Select type.
Select type.
Select type and function.
Select type.
Select type.
Select type.
Select type.
With double door.
With double door.
Select type. With double door.