

Sapa Door 2074

Fire resistant EI 60

Instructions.

Isolated doorpart in aluminium Sapa Door 2074.
Profile depth 74 mm.
Fire-resistance grade EI 60.
Outward opening/ inward opening, single door/ double door.
Narrow section/ modular section.
Rebate seal/ wool pile/ without threshold.
Surface treatment anodizing nature/ HX 10/ HX 20/ HX 30/ HX 40/ HX 50.
Surface treatment powder coating 60 µm, pretreatment acc. to Sapa std. Color NCS S/ RAL.
Approved glass acc. to Sapa, single glass/ double glass.
Approved in-fill panel acc. to Sapa.
Approved hinges/ barrel hinges acc. to Sapa.
Door handle.
Approved lock.
Approved lock striker.
Approved electric strikes.
Wiring loop.
Approved door closing device.
Approved panic or emergency device.
Flushbolt, single action/ double action acc. to Sapa std.
Automatic flushbolt acc. to Sapa std.
Door coordinator.
Installation and connections acc. to Sapa instructions.

Select alternative.
Select alternative.
Select alternative.
Select one type.
Select color.
Select alternative. Glass thickness max 44mm.
Select finishes.
Select alternative.
Select type.
Select type.
Select type and function.
Select type.
Select type.
Select type.
With double door.
With double door.
With double door.
Select type. With double door.