

Sapa Door 2086 with E-frame

Instructions.

Isolated doorpart in aluminium Sapa Door 2086 with E-frame.
Profile depth 86 mm.
Access control system, E-frame.
Outward opening/ inward opening, single door/ double door/ meeting door.
Narrow section/ modular section.
Non finger trapping function.
Rebate seal/ wool pile/ without threshold.
Surface treatment anodizing nature/ HX 5/ HX 10/ HX 20/ HX 30/ HX 40/ HX 50.
Surface treatment powder coating 60 μm , pretreatment acc. to Sapa std. Color NCS S/ RAL.
Double glass/ Triple glass/ toughened/ laminated/ sunscreen.
Infill panel F1/ F2/ F3/ F4, acc. to Sapa std.
Max. U-value for the whole construction.
Air tightness: no class/ class 2/ class 4 acc. to EN 12207.
Water tightness: no class/ class 4A/ class 9A acc. to EN 12208.
Sound insulation: Rw/ Rw+Ctr.
Hinges/ barrel hinges/ hidden hinges.
Pull handle/ push handle/ door handle.
Lock.
Lock striker.
Electric strikes.
Wireing loop.
Motor lock.
Door closing device.
Automatic door opening device.
Panic or emergency device.
Flushbolt, single action/ double action acc. to Sapa std.
Automatic flushbolt acc. to Sapa std.
Door coordinator.
Installation and connections acc. to Sapa instructions.

Select alternative.
Select alternative.
Or nor. Is not provided with barrel hinge.
Select alternative.
Select one type.
Select color.
Select alternative. Glass thickness 20-64mm.
Select finishes.
Select U-value.
Select class.
Select type and dB.
Select one alternative and surface treatment.
Select type.
Select type.
Select type.
Select type and function.
Select type.
Select type.
Select type.
With double door.
With double door.
With double door.
Select type. With double door.